

# 2005 TRUCK WHEELS, LUG NUTS & WHEEL VALVES

P/N	COLOR CODES	SALES CODE	SIZE	DESCRIPTION	USAGE	WEIGHT (LB)
52113234AA	E-coat	WF1	17X7.5X1.0	Spare	ND	32
52855013AA	E-coat	WDQ	16X7.0X1.0	Spare	ND	29.7
52855341AB		WPF	17X8.0X1.38	Chrome Clad Alum	HB	24
1A144TRMAA		WFJ	17X8.0X1.38	Cast Aluminum	HB	23
52113234AA	E-coat	WF1	17X7.5X1.07	Spare	HB	32
52000430AA	E-coat	WEE	17X7X1.07	Steel Wheel	HB	33.5
5JF60TRMAC	PAK	WF5	17X8X1.38	Cast Aluminum	HB	23.5
52013439AA	PAK	WGV	17X8.0X1	Chrome Clad Alum	ND	22.5
0XC99TRMAA	PAK	WD1	16X8.0X1.0	Aluminum Painted	ND	21.0
0YG95TRMAA	S4A	WNP	16X7.0X27.4mm	Steel Drop Center	ND	29.7
0XC98TRMAA	S4A	WDE	16X7.0X27.4mm	Full Face Steel	ND	30.2
5FV63TRMAE	S4A	WJ5	15X7.0X1.25	Full Face Steel	TJ	26.1
5EEB0TRMAF	PAK	WJW	15X7.0X1.25	Cast Aluminum Painted	TJ	19.1
5JL73TRMAA	PAK	WJ4	15x8.0x1.00	Cast Aluminum Painted	TJ	17.5
5HP23TRMAB	PAK	WDY	16x8.0x0.50	Cast Aluminum Painted	TJ	25.4
5GY15TRMAA	S4A	WD2	17X7.5X1.75	Steel Wheel	DR2,3,7,8 SRW	40.7
52121325AA	E-coat	WF1	17X7.5X1.75	Spare	DR2,3,7,8 SRW	40.7
52110366AB		WGS	17X8.0X1.70	Chrome Clad Steel	DR2,3,7,8 SRW	42.0
52013663AA		WGD	17X8.0X1.70	Forged Aluminum	DR2,3,7,8 SRW	24.5
52121267AA		WD4	17X6.0X5.35	Dual Steel	DR3,8 SRW	41.5
52110457AB		WF1	17X7.0X1.00	Spare	DR1,6	32.0
52113265AC		WF2	17X8.0X1.00	FF Steel, Clad	DR1,6	37.7
5HW99TRMAB	S4A	WFV	17X8.0X1.00	Cast Aluminum	DR1,6	35.5
0XJ45TRMAA	S4A	WEA	17X7.0X1.00	Base Steel	DR1,6	32
5HK22TRMAF	PAK	WF4	17X8.0X1.00	Cast Aluminum	DR1,6	28.2
52110166AD		WF3	20X9.0X0.75	Cast Aluminum, Clad	DR1,6	36.9
52110356AC		WFG	20X9.0X0.75	Cast Aluminum, Clad	DR1,6	37.9
52110456AB		WGA	20X8.0X0.75	Spare	DR1,6	43.8

4A, S4A = Argent

PAK = Liquid Sparkle Silver

NA = Information not available at time of printing.

YFD = sparkle pewter

ALC = Alcoa

REY = Reynolds

SUP = Superior

ARE = American Racing

HLA = Hayes Lemmerz aluminum

HLF = Hayes Lemmerz fabricated

MER = Meritor

P/N	USED ON	DESCRIPTION	USAGE	TORQUE RANGE (LB-FT)	RECOMMENDED TORQUE (LB-FT)	WEIGHT PER NUT (LB)
06036433AA	GV, WD1, WNP, W	9/16-18, 60 DEGREES	ND	120-150	135	0.146
06036310AA	ALL TJ	7/20-1.38, 60 DEGREES	TJ	100-115	115	0.084
06036340AA	ALL DR1,6	9/16-18, 60 DEGREES	DR1,6	120-150	135	0.146
06036503AA	WEE	9/16-18, 60 DEGREES	HB	120-150	135	0.146
06036433AA	ALL DR & WF5	9/16-18, 60 DEGREES	ALL DR & HB	120-150	135	0.146
6034727	WGS, WD2	9/16-18, 60 DEGREES	DR2,3,7,8 SRW	120-150	135	0.146
6034727	WGD	9/16-18, 60 DEGREES	DR2,3,7,8 SRW	120 - 150	135	0.146
6034726	WD4	9/16-18, FLAT	DR3,8 DRW	130 - 160	145	0.26

P/N	USED ON	DESCRIPTION	USAGE	WEIGHT PER VALVE (LB)
02073355	WCP, WJM	VALVE-RUBBER 1.25		0.024
	WJA, ALL DR1,6		DR1,6	
02073355	ALL	VALVE-RUBBER 1.25	AN1/5	0.024
02073355	ALL	VALVE-RUBBER 1.25	TJ	0.024
0474327AA	ALL	VALVE-RUBBER 1.5	HB	0.026
52057949AB	ALL	VALVE-600 HP	DR2,3,7,8	0.030