


DAKOTA CLUB CAB 131.3"WB 4X2

POSITION THE MOUSE OVER THE CODE FOR INSTANT DIMENSION



PLAN & SIDE VIEW



CHARTS

Site Map

Main Menu

Dakota Home

PRINT


ALL

IN

OUT

DAKOTA CLUB CAB 131.3"WB 4X2

POSITION THE MOUSE OVER THE CODE FOR INSTANT DIMENSION



FRONT & REAR VIEW



CHARTS

[Site Map](#)

[Main Menu](#)

[Dakota Home](#)

PRINT

ALL

IN

OUT

Code	Description	mm	in
L50	SgRP Couple distance (1-2)	613.0	24.1
L103	Vehicle Length	5558.2	218.8
L403	Front of Bumper to Back of Cab	3320.2	130.7
L410	Cab Length	1976.6	77.8
L504	Cab to Pickup Body	23.0	0.9
TRL1	Rear Bumper to Back of Cab	2238.0	88.1
TRL2	Fuel Tank Length	1606.4	63.2

Code	Description	mm	in
CH16	Box Bed to Cab Roof	531.5	20.9
CH17	Box Floor to Cab Roof	982.0	38.7
CH18	Steering Column Angle	24.0°	24.0°
CH514	Box Floor to Top of Fuel Tank	99.5	3.9
H6	SgRP-Front to Windshield Lwr DLO	460.0	18.1
H18	Steering Wheel Angle	24.0°	24.0°
H61	Effective Head Room Front	1005.3	39.6
H63	Effective Head Room Second	928.3	36.5
H122	Window Slope Angle - Windshield	55.1°	55.1°

Code	Description	mm	in
TRW1	Outside Rail to Fuel Tank (inside)	434.8	17.1
W106	Front Fender Width	1825.4	71.9
W107	Rear Fender Width	1883.3	74.1
W116	Body Width - maximum	1887.6	74.3
W117	Body Width At SgRP - Front	1821.7	71.7
W120	Vehicle Width - Front Doors Open	3688.4	145.2
W121	Vehicle Width - Rear Doors Open	2952.8	116.3
W201	Cargo Width - Wheelhouse	1146.9	45.2
W410	Vehicle Width - Mirrors (std)	2084.8	82.1
W410A	Vehicle Width - Mirrors (opt)	2190.9	86.3


TIRE CHART

FRONT & REAR VIEW

PLAN & SIDE VIEW
[Site Map](#)
[Main Menu](#)
[Dakota Home](#)
PRINT
ALL
IN
OUT

Code	Description	245/70R16		255/65R16		265/60R18		265/70R16		275/60R17	
		Metric	English	Metric	English	Metric	English	Metric	English	Metric	English
CH511	Bottom of Open Hood to Ground	1689.8 mm	66.5 in	1700.8 mm	67.0 in	1702.7 mm	67.0 in	1704.3 mm	67.1 in	1697.9 mm	66.8 in
CHR22	Turn Circle Diameter (feet/meters)*		43.3 ft		43.3 ft		43.3 ft		43.3 ft		43.3 ft
CL513	Rear Axle to Inside Box at Rear	1014.6 mm	39.9 in	1014.6 mm	39.9 in	1014.6 mm	39.9 in	1014.6 mm	39.9 in	1014.6 mm	39.9 in
H5	SgRP-Front to Ground	772.9 mm	30.4 in	784.6 mm	30.9 in	786.1 mm	30.9 in	787.1 mm	31.0 in	780.8 mm	30.7 in
H10	SgRP-Second to Ground	833.2 mm	32.8 in	845.0 mm	33.3 in	846.5 mm	33.3 in	847.1 mm	33.4 in	840.9 mm	33.1 in
H101	Vehicle Height (curbLoad)	1727.4 mm	68.0 in	1739.2 mm	68.5 in	1740.7 mm	68.5 in	1741.4 mm	68.6 in	1735.2 mm	68.3 in
H103	Front Bumper to Ground (curbwt.)	306.9 mm	12.1 in	318.0 mm	12.5 in	319.9 mm	12.6 in	321.5 mm	12.7 in	315.0 mm	12.4 in
H105	Rear Bumper to Ground (curbwt.)	463.1 mm	18.2 in	475.6 mm	18.7 in	476.7 mm	18.8 in	476.7 mm	18.8 in	470.6 mm	18.5 in
H106	Angle of Approach	22.1 deg	22.1 deg	22.9 deg	22.9 deg	22.9 deg	22.9 deg	23.1 deg	23.1 deg	22.7 deg	22.7 deg
H107	Angle of Departure	21.9 deg	21.9 deg	22.4 deg	22.4 deg	22.5 deg	22.5 deg	22.5 deg	22.5 deg	22.3 deg	22.3 deg
H108	Static Load-Tire Radius-Front*	334.8 mm	13.2 in	345.4 mm	13.6 in	346.2 mm	13.6 in	348.0 mm	13.7 in	342.6 mm	13.5 in
H109	Static Load-Tire Radius-Rear*	334.8 mm	13.2 in	345.4 mm	13.6 in	346.2 mm	13.6 in	348.0 mm	13.7 in	342.6 mm	13.5 in
H130	Step Height - Front (curbweight)	502.8 mm	19.8 in	514.3 mm	20.2 in	515.9 mm	20.3 in	517.1 mm	20.4 in	510.7 mm	20.1 in
H131	Step Height - Second (curbweight)	527.8 mm	20.8 in	539.5 mm	21.2 in	541.0 mm	21.3 in	541.9 mm	21.3 in	535.6 mm	21.1 in
H147	Ramp Breakover Angle	18.7 deg	18.7 deg	19.6 deg	19.6 deg	19.7 deg	19.7 deg	19.8 deg	19.8 deg	19.4 deg	19.4 deg
H148	Suspension or Axel to Ground-Front	187.1 mm	7.4 in	198.4 mm	7.8 in	200.2 mm	7.9 in	201.6 mm	7.9 in	195.1 mm	7.7 in
H153	Suspension or Axel to Ground-Rear	188.6 mm	7.4 in	200.7 mm	7.9 in	202.0 mm	8.0 in	202.4 mm	8.0 in	196.2 mm	7.7 in
H195	Liftover Height	1230.5 mm	48.4 in	1242.9 mm	48.9 in	1244.0 mm	49.0 in	1244.1 mm	49.0 in	1238.0 mm	48.7 in
H250	Open Tailgate to Ground	792.3 mm	31.2 in	804.8 mm	31.7 in	805.9 mm	31.7 in	805.8 mm	31.7 in	799.8 mm	31.5 in
L101	Wheelbase	3335.3 mm	131.3 in	3335.3 mm	131.3 in	3335.3 mm	131.3 in	3335.3 mm	131.3 in	3335.3 mm	131.3 in
L104	Overhang-Front	983.1 mm	38.7 in	983.1 mm	38.7 in	983.1 mm	38.7 in	983.1 mm	38.7 in	983.1 mm	38.7 in
L105	Overhang-Rear	1239.8 mm	48.8 in	1239.8 mm	48.8 in	1239.8 mm	48.8 in	1239.8 mm	48.8 in	1239.8 mm	48.8 in
L114	Front Wheel to Front SgRP c/l	1457.1 mm	57.4 in	1457.1 mm	57.4 in	1457.1 mm	57.4 in	1457.1 mm	57.4 in	1457.1 mm	57.4 in
L404	Cab to Rear Axle	998.2 mm	39.3 in	998.2 mm	39.3 in	998.2 mm	39.3 in	998.2 mm	39.3 in	998.2 mm	39.3 in
TRL3	Rear Wheel Center line to Fuel Tank	148.4 mm	5.8 in	148.4 mm	5.8 in	148.4 mm	5.8 in	148.4 mm	5.8 in	148.4 mm	5.8 in
W101	Tire Track-front	1594.5 mm	62.8 in	1594.5 mm	62.8 in	1594.5 mm	62.8 in	1594.5 mm	62.8 in	1594.5 mm	62.8 in
W102	Tire Track-rear	1598.0 mm	62.9 in	1598.0 mm	62.9 in	1598.0 mm	62.9 in	1598.0 mm	62.9 in	1598.0 mm	62.9 in


CHART
[Site Map](#)
[Main Menu](#)
[Dakota Home](#)
[PRINT](#)
