


RAM OCCUPANT RESTRAINT SYSTEM INFORMATION



Next Generation Driver and Front-Passenger Air Bag* System

Air Bag System Verification

After modification work is complete, the modifier must confirm air bag system readiness, as follows:

- Turn the ignition key on. The air bag lamp in the Instrument cluster will illuminate for six to eight seconds, and then turn off. If the air bag lamp fails to illuminate, cycles on and off, or does not turn off, the modifier must have the vehicle repaired by a DaimlerChrysler Motors Corporation dealership before shipping.

Passenger Air Bag On/Off Switch

For 2005, on all Ram Standard Cab pickups, a passenger air bag on/off switch with indicator lamp is installed on the instrument panel, as allowed by NHTSA rulemaking. The driver can activate or deactivate the passenger air bag by inserting and turning an ignition key in the switch, observing if its indicator lamp is *ON* or *OFF* and then immediately removing the ignition key from the ON/OFF switch. **THIS SWITCH MUST REMAIN INTACT AND MAY NOT BE USED FOR ANY OTHER PURPOSE. UNDER NO CIRCUMSTANCES SHOULD THE IGNITION KEY BE LEFT IN THE FRONT PASSENGER AIR BAG ON/OFF SWITCH.** For some of the 2500 and 3500 applications the switch may not be required (Mexican Sales, etc.) and therefore not present.

Air Bag Diagnostic Module

The Air Bag Diagnostic Module is located under the instrument panel on the forward end of the transmission tunnel, and is covered by a plastic trim cover. Care must be taken not to disturb this module for any reason. It is also important that no modifications are made to the tunnel sheet metal, as this may affect the performance of the air bag system.

Air Bag Wiring

All air bag wiring must remain intact and may not be used for any other purpose.

Location of Air Bag System Components

It is imperative that all air bag system components remain in their original location and orientation. Any removal or relocation of components, such as the diagnostic module or the instrument panel wiring, may be detrimental to air bag system performance and is prohibited.

Knee Blocker/Lower Steering Column Cover

The lower steering column cover area and glove box, also known as "knee blockers," are integral parts of the air bag restraint system. These areas include energy-absorbing features and must not be removed or modified in any manner. This includes the attachment of any auxiliary switches, such as those for fog lamps or snowplow accessories.

Steering Column Collapse Zone

The steering column in this vehicle is designed to collapse axially under a compressive load in the event of a severe frontal impact. In order for the steering column to perform properly, it must not be modified in any manner. This includes all componentry, which is adjacent to the steering column, such as the shrouds, the upper support bracketry, and the toe board attachment. Caution must also be exercised to ensure that nothing is placed in the axial path of the steering column, or that any of the designed clearance gaps are disturbed.

Front Bumper System

Since the crash sensing of the air bag system is tuned, in part, to the front bumper, the original front bumper system (beam, brackets and fascia) of vehicles with a

RAM OCCUPANT RESTRAINT SYSTEM INFORMATION

modifications or additions to the bumper (i.e., bumper-mounted bicycle racks) are permitted.


Warning Labels

Removing or covering air bag warning labels is prohibited. Labels (glove box, visors, etc.) are used to alert vehicle operators and service personnel that:

- The vehicle is equipped with an air bag, but always use seat belts and child restraints
- A backseat is the safest place for children under 12
- Never put a rearward-facing child seat in the front passenger seat unless the air bag is turned off
- Caution must be exercised when the vehicle is serviced, since improper procedures may cause inadvertent air bag deployment
- The system must be inspected at regular intervals, or when service is indicated by readiness lamp operation
- If a sun visor is replaced, the replacement visor must be equipped with an equivalent warning label

Miscellaneous Requirements

Any components added to the occupant compartment must not break loose during a 30-mph barrier impact test. A plot of the average passenger compartment deceleration with respect to time is shown in the pulse curve below.



Further, any pulse curve information can be retrieved from the National Highway Traffic Safety Administration at the address below:

National Highway Traffic Safety Administration

Technical References Division

NAD-40, Room 5108

400 7th Street, S.W.

Washington, D.C. 20590

Telephone: (800) 445-0197

Working hours: 7:45 a.m. - 4:15 p.m. EST

* Certified to the Federal Regulations that allow less forceful front air bags. Always use seat belts. Children 12 and under can be in the front seat only with the passenger air bag turned off in Ram

Pickups correctly using an infant or child restraint system, or a seat belt that is right for their age and size

Upgraded Driver Restraint System

1. Disconnect battery negative terminal before removing the driver's side seat belt retractor.
2. The OEM driver's side retractor cover must be used unless approval is given from DaimlerChrysler Modified Vehicles Engineering for an alternate retractor cover.
3. Store driver's side retractor in a secure area when removed from the vehicle to avoid damage or loss.
4. The driver's side retractor must be connected to the Air Bag Electronic Control Module located under the driver's seat.