

# VEHICLE PLACARD

## VEHICLE PLACARD

The following information is displayed on the Vehicle Placard: Seating Capacities (total, front and rear), Combined maximum cargo and occupant weight, Original Tire Size (front, rear and spare), and Cold Tire Inflation Pressure (front, rear and spare).



For various fully certified vehicles, this label can be found on the driver's side B-Pillar of the vehicle.

When altering a fully certified vehicle, Upfitters/Alterers must affix a new placard, containing accurate information for the altered vehicle, over the placard installed by the vehicle manufacturer (see sample on right), so as to obscure the original placard.

Upfitters/Alterers must affix their own placard in accordance with FMVSS 110, with vehicle capacity weight and seating designations "as finally manufactured" when completing an Incomplete Vehicle. Upfitters/Alterers must use the information from the front of the Incomplete Vehicle Document (see ICVD in Dodge Ram Second Stage Manufacturers section of the 2005 Dodge Body Builder Guide), as required by § 568.4 (Code of Federal Regulations 49 part 568.4) to be provided by incomplete and intermediate vehicle manufacturers and the information particular to their role in the manufacture of the vehicle.

DaimlerChrysler is not required by Federal regulation to update the label once the vehicle is completed by an Upfitter/Alterer.

### Example:

TIRE AND LOADING INFORMATION				
	SEATING CAPACITY — TOTAL	5	FRONT 2	REAR 3
	THE COMBINED WEIGHT OF OCCUPANTS AND CARGO SHOULD NEVER EXCEED			
	XXX KG OR XXX LBS.			
TIRE	FRONT	REAR	SPARE	
ORIGINAL TIRE SIZE	P195/70R14	P195/70R14	T125/70D15	
COLD TIRE INFLATION PRESSURE	200kPa, 29PSI	200kPa, 29PSI	420kPa, 60PSI	
SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION 				4N109268