


REGULAR CAB 1500 120.5"WB 4x2

POSITION THE MOUSE OVER THE CODE FOR INSTANT DIMENSION



 **PLAN & SIDE VIEW**

 **CHARTS**

 **Site Map**

 **Main Menu**

 **Ram Home**

PRINT


 **ALL**

 **IN**

 **OUT**

REGULAR CAB 1500 120.5"WB 4x2

POSITION THE MOUSE OVER THE CODE FOR INSTANT DIMENSION



 **FRONT & REAR VIEW**

 **CHARTS**

 **Site Map**

 **Main Menu**

 **Ram Home**

PRINT

 **ALL**

 **IN**

 **OUT**

REGULAR CAB 1500 120.5"WB 4X2

Code	RAM REG CAB 6.5 BOX 120.5WB	Metric	English
L403	Front of Bumper to Back of Cab	3122.2 mm	122.9 in
L410	Cab Length	1860.6 mm	73.3 in
L504	Cab to Pickup Body	17.4 mm	0.7 in
TRL1	Rear Bumper to Back of Cab	2153.2 mm	84.8 in
TRL2	Fuel Tank Length	1152.9 mm	45.4 in

Code	RAM REG CAB 6.5 BOX 120.5WB	Metric	English
CH16	Top of Box to Cab Roof	590.8 mm	23.3 in
CH17	Box Floor to Cab Roof	1114.0 mm	43.9 in
CH18	Steering Column Angle	22.9 deg	22.9 deg
CH514	Box Floor to Top of Fuel Tank	83.8 mm	3.3 in
H6	SgRP-Front to Windshield Lower DLO	446.2 mm	17.6 in
H18	Steering Wheel Angle	26.7 deg	26.7 deg
H61	Effective Head Room Front	1035.9 mm	40.8 in
H122	Window Slope Angle-Windshield	56.9 deg	56.9 deg

Code	RAM REG CAB 6.5 BOX 120.5WB	Metric	English
TRW1	Outside Rail to Fuel Tank(inside)	364.6 mm	14.4 in
W106	Front Fender Width	2020.7 mm	79.6 in
W107	Rear Fender Width	2021.7 mm	79.6 in
W116	Body Width-maximum	2021.8 mm	79.6 in
W117	Body Width At SgRP-Front	2018.9 mm	79.5 in
W120	Vehicle Width-Front Doors Open	4138.4 mm	162.9 in
W201	Cargo Width-Wheelhouse	1295.4 mm	51.0 in
W410	Vehicle Width-Mirrors(std)	2396.2 mm	94.3 in
W410A	Vehicle Width-Mirrors(opt)	2587.1 mm	101.9 in
W410B	Vehicle Width-Mirrors(trailer)	2751.4 mm	108.3 in

 **TIRE CHART**

 **FRONT & REAR VIEW**

 **PLAN & SIDE VIEW**

 **Site Map**

 **Main Menu**

 **Ram Home**

PRINT

 **ALL**

 **+**
IN

 **-**
OUT

REGULAR CAB 1500 120.5"WB 4X2

Code	RAM REG CAB 6.5 BOX 1500 4X2 120.5WB	P245/70R17		P265/70R17	
		Metric	English	Metric	English
CH511	Bottom of Open Hood to Ground	1922.6 mm	75.7 in	1939.8 mm	76.4 in
CHR22	Turn Circle Diameter (feet/meters)*	12.6 m	41.5 ft	12.6 m	41.5 ft
CL513	Rear Axle to Inside Box at Rear	1016.3 mm	40.0 in	1016.3 mm	40.0 in
H5	SgRP-Front to Ground	895.6 mm	35.3 in	912.8 mm	35.9 in
H101	Vehicle Height(curbLoad)	1874.1 mm	73.8 in	1891.3 mm	74.5 in
H103	Front Bumper to Ground(curbwt.)	242.7 mm	9.6 in	259.9 mm	10.2 in
H105	Rear Bumper to Ground(curbwt.)	505.8 mm	19.9 in	523.0 mm	20.6 in
H106	Angle of Approach	15.6 deg	15.6 deg	16.7 deg	16.7 deg
H107	Angle of Departure	24.2 deg	24.2 deg	25.1 deg	25.1 deg
H108	Static Load-Tire Radius-Front*	345.0 mm	13.6 in	362.2 mm	14.3 in
H109	StaticLoad-Tire Radius-Rear*	345.0 mm	13.6 in	362.2 mm	14.3 in
H130	Step Height - Front(curbweight)	522.5 mm	20.6 in	539.7 mm	21.2 in
H147	Ramp Breakover Angle	19.8 deg	19.8 deg	21.4 deg	21.4 deg
H148	Suspension or Axel to Ground-Front	208.6 mm	8.2 in	225.8 mm	8.9 in
H153	Suspension or Axel to Ground-Rear	187.9 mm	7.4 in	205.1 mm	8.1 in
H195	Liftover Height	1340.0 mm	52.8 in	1357.2 mm	53.4 in
H250	Open Tailgate to Ground	834.7 mm	32.9 in	851.9 mm	33.5 in
L101	Wheelbase	3062.0 mm	120.6 in	3062.0 mm	120.6 in
L104	Overhang-Front	997.9 mm	39.3 in	997.9 mm	39.3 in
L105	Overhang-Rear	1215.5 mm	47.9 in	1215.5 mm	47.9 in
L114	Front Wheel to Front SgRP c/l	1475.7 mm	58.1 in	1475.7 mm	58.1 in
L404	Cab to Rear Axle	937.7 mm	36.9 in	937.7 mm	36.9 in
TRL3	Rear Wheel Center line to Fuel Tank	172.8 mm	6.8 in	172.8 mm	6.8 in
W101	Tire Track-front	1727.0 mm	68.0 in	1727.0 mm	68.0 in
W102	Tire Track-rear	1724.7 mm	67.9 in	1724.7 mm	67.9 in



[Site Map](#)

[Main Menu](#)

[Ram Home](#)

[PRINT](#)

[ALL](#)

[IN](#)

[OUT](#)