



QUAD CAB 2500 160.5"WB 4x2**POSITION THE MOUSE OVER THE CODE FOR INSTANT DIMENSION****PLAN & SIDE VIEW****CHARTS**[Site Map](#)[Main Menu](#)[Ram Home](#)[PRINT](#)[ALL](#)[IN](#)[OUT](#)

QUAD CAB 2500 160.5"WB 4x2

POSITION THE MOUSE OVER THE CODE FOR INSTANT DIMENSION



FRONT & REAR VIEW



CHARTS

QUAD CAB 2500 160.5"WB 4x2

Code	RAM QUAD CAB 8.0 BOX 160.5WB	Metric	English
L50	SgRP Couple distance(1-2)	787.4 mm	31.0 in
L103	Vehicle Length	6342.2 mm	249.7 in
L403	Front of Bumper to Back of Cab	3630.2 mm	142.9 in
L410	Cab Length	2368.6 mm	93.3 in
L504	Cab to Pickup Body	17.4 mm	0.7 in
TRL1	Rear Bumper to Back of Cab	2712.0 mm	106.8 in
TRL2	Fuel Tank Length	1637.3 mm	64.5 in

Code	RAM QUAD CAB 8.0 BOX 160.5WB	Metric	English
CH16	Top of Box to Cab Roof	600.3 mm	23.6 in
CH17	Box Floor to Cab Roof	1123.6 mm	44.2 in
CH18	Steering Column Angle	22.9 deg	22.9 deg
CH514	Box Floor to Top of Fuel Tank	83.8 mm	3.3 in
H6	SgRP-Front to Windshield Lower DLO	446.2 mm	17.6 in
H18	Steering Wheel Angle	26.7 deg	26.7 deg
H61	Effective Head Room Front	1040.9 mm	41.0 in
H63	Effective Head Room Second	1016.3 mm	40.0 in
H122	Window Slope Angle-Windshield	56.9 deg	56.9 deg

Code	RAM QUAD CAB 8.0 BOX 160.5WB	Metric	English
TRW1	Outside Rail to Fuel Tank(inside)	402.4 mm	15.8 in
W106	Front Fender Width	2020.7 mm	79.6 in
W107	Rear Fender Width	2021.6 mm	79.6 in
W116	Body Width-maximum	2021.8 mm	79.6 in
W117	Body Width At SgRP-Front	2019.8 mm	79.5 in
W120	Vehicle Width-Front Doors Open	3805.1 mm	149.8 in
W121	Vehicle Width-Rear Doors Open	3546.5 mm	139.6 in
W201	Cargo Width-Wheelhouse	1295.4 mm	51.0 in
W410	Vehicle Width-Mirrors(std)	2396.2 mm	94.3 in
W410A	Vehicle Width-Mirrors(opt)	2587.1 mm	101.9 in
W410B	Vehicle Width-Mirrors(trailer)	2751.4 mm	108.3 in


TIRE CHART

FRONT & REAR VIEW

PLAN & SIDE VIEW
[Site Map](#)
[Main Menu](#)
[Ram Home](#)
[PRINT](#)


QUAD CAB 2500 160.5"WB 4x2

09/01/2006

Code	Description	LT245/70R17		LT265/70R17	
		Metric	English	Metric	English
CH511	Bottom of Open Hood to Ground	1937.6 mm	76.3 in	1946.2 mm	76.6 in
CHR22	Turn Circle Diameter (feet/meters)*	15.3 m	43.6 ft	15.3 m	44.1 ft
CL513	Rear Axle to Inside Box at Rear	1067.2 mm	42.0 in	1067.2 mm	42.0 in
H5	SgRP-Front to Ground	896.7 mm	35.3 in	905.3 mm	35.6 in
H10	SgRP-Second to Ground	923.1 mm	36.3 in	931.7 mm	36.7 in
H101	Vehicle Height(curbLoad)	1887.9 mm	74.3 in	1896.5 mm	74.7 in
H103	Front Bumper to Ground(curbwt.)	258.3 mm	10.2 in	266.9 mm	10.5 in
H105	Rear Bumper to Ground(curbwt.)	507.2 mm	20.0 in	515.8 mm	20.3 in
H106	Angle of Approach	16.6 deg	16.6 deg	17.1 deg	17.1 deg
H107	Angle of Departure	23.3 deg	23.3 deg	23.7 deg	23.7 deg
H108	Static Load-Tire Radius-Front*	363.5 mm	14.3 in	372.1 mm	14.6 in
H109	StaticLoad-Tire Radius-Rear*	363.5 mm	14.3 in	372.1 mm	14.6 in
H130	Step Height - Front(curbweight)	527.4 mm	20.8 in	536.0 mm	21.1 in
H131	Step Height - Second(curbweight)	546.3 mm	21.5 in	554.9 mm	21.8 in
H147	Ramp Breakover Angle	15.1 deg	15.1 deg	15.7 deg	15.7 deg
H148	Suspension or Axel to Ground-Front	190.3 mm	7.5 in	198.9 mm	7.8 in
H153	Suspension or Axel to Ground-Rear	180.2 mm	7.1 in	188.8 mm	7.4 in
H195	Liftover Height	1342.2 mm	52.8 in	1350.8 mm	53.2 in
H250	Open Tailgate to Ground	836.3 mm	32.9 in	844.9 mm	33.3 in
L101	Wheelbase	4076.9 mm	160.5 in	4076.9 mm	160.5 in
L104	Overhang-Front	999.0 mm	39.3 in	999.0 mm	39.3 in
L105	Overhang-Rear	1266.3 mm	49.9 in	1266.3 mm	49.9 in
L114	Front Wheel to Front SgRP c/l	1474.6 mm	58.1 in	1474.6 mm	58.1 in
L404	Cab to Rear Axle	1445.6 mm	56.9 in	1445.6 mm	56.9 in
TRL3	Rear Wheel Center line to Fuel Tank	172.7 mm	6.8 in	172.7 mm	6.8 in
W101	Tire Track-front	1742.4 mm	68.6 in	1742.4 mm	68.6 in
W102	Tire Track-rear	1731.5 mm	68.2 in	1731.5 mm	68.2 in



CHART

[Site Map](#)

[Main Menu](#)

[Ram Home](#)

PRINT

ALL

IN

OUT