

RAM FLUID CAPACITIES

Fuel	Liters	Gallons	Front Axle	Liters	Pints
1500 Short Bed	98.42	26.00	C205F	1.66	3.50
1500 Long Bed	132.49	35.00	9.25 AA	2.25	4.75
2500 Short Bed	128.70	34.00	Rear Axle		
2500 Long Bed	132.49	35.00	9.25 ⁽²⁾	2.32	4.90
3500 Short Bed	128.70	34.00	10.5 AA	2.25	4.75
3500 Long Bed	132.49	35.00	11.5 AA	3.62	7.65
Engine Oil			Transmission Fluid		
	Liters	Quarts		Liters	Pints
3.7L Magnum V6	4.73	5.00	NV3500 5-Speed Manual 4x2	2.27	4.80
4.7L Magnum V8	5.68	6.00	NV3500 5-Speed Manual 4x4	1.99	4.20
5.7L Magnum V8	6.62	7.00	NV4500 5-Speed Manual	3.79	8.00
5.9L Magnum V8	4.73	5.00	NV5600 6-Speed Manual	4.50	9.50
8.0L Magnum V10	6.62	7.00	46RE 4-Speed Automatic Service Fill	3.79	8.00
5.9L Diesel	11.36	12.00	46RE 4-Speed Automatic O-haul Fill ⁽³⁾	8.99 - 9.46	19.00 - 20.00
Cooling System Fluid ⁽¹⁾			47RE 4-Speed Automatic Service Fill	3.79	8.00
	Liters	Quarts	47RE 4-Speed Automatic O-haul Fill ⁽³⁾	13.7 - 15.61	29.00 - 33.00
3.7L Magnum V6	16.00	17.00	48RE 4-Speed Automatic Service Fill	3.79	8.00
4.7L Magnum V8	16.00	17.00	48RE 4-Speed Automatic O-haul Fill ⁽³⁾	13.7 - 15.61	29.00 - 33.00
5.7L Magnum V8	17.70	18.70	45RFE & 545 RFE 5-Speed Automatic		
5.9L Magnum V8	17.70	18.70	Service Fill 4x2	5.20	11.00
8.0L Magnum V10	22.90	24.20	45RFE & 545 RFE 5-Speed Automatic		
5.9L Diesel	26.50	28.00	Service Fill 4x4	6.15	13.00
Transfer Case			45RFE & 545 RFE 5-Speed Automatic		
	Liters	Pints	O-haul Fill ⁽³⁾	13.7 - 15.61	29.00 - 33.00
NV241	1.61	3.40			
NV243	1.61	3.40			
NV271	1.89	4.00			
NV273	1.89	4.00			

(1) Includes 0.9L (1.0 quarts) for coolant reservoir.

(2) If equipped with Trac-lok add 0.25 pints (118mL) of Limited Slip Additive.

(3) Dry fill capacity depending on type and size of internal cooler, length and inside diameter of cooler lines, or use of an auxiliary cooler, these figures may vary.