

# CHASSIS CAB 4500/5500 192.5"WB 108.2CA FUEL TANK

## NOTE:

### AUXILLARY FUEL PORT

An auxillary fuel tap is provided on gas and diesel fuel tanks to provide fuel for secondary power systems. This is located on top of the fuel pump module and is sealed with a connector. This system will not drain the vehicle fuel completely. There will be sufficient fuel to drive back from the worksite.

Utilize due care when installing a secondary fuel system. Install a check valve in line to prevent OBD11 system faults. Installing a secondary fuel port may affect the vehicles ability to comply with F/CMVSS 301. Final Stage Manufacturer assumes all responsibility for fuel system modifications and system compliance.

### ***\*SELECT A FUEL TANK DETAIL***



**REAR 52.2**




**MID-SHIP 22.5**

# CHASSIS CAB 4500/5500

## MID-SHIP 22.5 GALLON 192.5"WB 108.2CA FUEL TANK

PRELIMINARY

FINAL DATA WILL BE POSTED BY SEPTEMBER 2007



REAR 52.2



NOTE

[Site Map](#)

[Main Menu](#)


[Chassis Cab Home](#)

PRINT

ALL

IN

OUT

**CHASSIS CAB 4500/5500****REAR 52.2 GALLON 192.5"WB 108.2CA FUEL TANK****MID-SHIP 22.5****NOTE**
**Site Map**
**Main Menu**
**Chassis Cab Home**
**PRINT**
**ALL**
**IN**
**OUT**

PRELIMINARY

FINAL DATA WILL BE POSTED BY SEPTEMBER 2007