



QUAD CAB 2500 140.5"WB 4x2**POSITION THE MOUSE OVER THE CODE FOR INSTANT DIMENSION****PLAN & SIDE VIEW****CHARTS****Site Map****Main Menu****Ram Home****PRINT**
ALL
IN
OUT

QUAD CAB 2500 140.5"WB 4x2

POSITION THE MOUSE OVER THE CODE FOR INSTANT DIMENSION



FRONT & REAR VIEW



CHARTS

QUAD CAB 2500 140.5"WB 4x2

09/01/2006

| Code | RAM QUAD CAB 6.5 BOX 140.5WB | Metric | English |
|------|--------------------------------|-----------|----------|
| L50 | SgRP Couple distance(1-2) | 787.4 mm | 31.0 in |
| L103 | Vehicle Length | 5783.4 mm | 227.7 in |
| L403 | Front of Bumper to Back of Cab | 3630.2 mm | 142.9 in |
| L410 | Cab Length | 2314.1 mm | 91.1 in |
| L504 | Cab to Pickup Body | 17.4 mm | 0.7 in |
| TRL1 | Rear Bumper to Back of Cab | 2153.2 mm | 84.8 in |
| TRL2 | Fuel Tank Length | 1152.9 mm | 45.4 in |

| Code | RAM QUAD CAB 6.5 BOX 140.5WB | Metric | English |
|-------|------------------------------------|-----------|----------|
| CH16 | Top of Box to Cab Roof | 600.3 mm | 23.6 in |
| CH17 | Box Floor to Cab Roof | 1123.6 mm | 44.2 in |
| CH18 | Steering Column Angle | 22.9 deg | 22.9 deg |
| CH514 | Box Floor to Top of Fuel Tank | 83.8 mm | 3.3 in |
| H6 | SgRP-Front to Windshield Lower DLO | 446.2 mm | 17.6 in |
| H18 | Steering Wheel Angle | 26.7 deg | 26.7 deg |
| H61 | Effective Head Room Front | 1042.6 mm | 41.0 in |
| H63 | Effective Head Room Second | 1017.2 mm | 40.0 in |
| H122 | Window Slope Angle-Windshield | 56.9 deg | 56.9 deg |

| Code | RAM QUAD CAB 6.5 BOX 140.5WB | Metric | English |
|-------|-----------------------------------|-----------|----------|
| TRW1 | Outside Rail to Fuel Tank(inside) | 434.2 mm | 17.1 in |
| W106 | Front Fender Width | 2020.7 mm | 79.6 in |
| W107 | Rear Fender Width | 2021.6 mm | 79.6 in |
| W116 | Body Width-maximum | 2021.8 mm | 79.6 in |
| W117 | Body Width At SgRP-Front | 2019.8 mm | 79.5 in |
| W120 | Vehicle Width-Front Doors Open | 3805.1 mm | 149.8 in |
| W121 | Vehicle Width-Rear Doors Open | 3546.5 mm | 139.6 in |
| W201 | Cargo Width-Wheelhouse | 1295.4 mm | 51.0 in |
| W410 | Vehicle Width-Mirrors(std) | 2396.2 mm | 94.3 in |
| W410A | Vehicle Width-Mirrors(opt) | 2587.1 mm | 101.9 in |
| W410B | Vehicle Width-Mirrors(trailer) | 2751.4 mm | 108.3 in |



TIRE CHART



FRONT & REAR VIEW



PLAN & SIDE VIEW

Site Map

Main Menu

Ram Home

PRINT



QUAD CAB 2500 140.5"WB 4x2

09/01/2006

| Code | RAM QUAD CAB 6.5 BOX 2500 4X2 140.5WB | LT245/70R17 | | LT265/70R17 | |
|-------|---------------------------------------|-------------|----------|-------------|----------|
| | | Metric | English | Metric | English |
| CH511 | Bottom of Open Hood to Ground | 1935.7 mm | 76.2 in | 1944.4 mm | 76.6 in |
| CHR22 | Turn Circle Diameter (feet/meters)* | 14.3 m | 47.0 ft | 14.3 m | 47.0 ft |
| CL513 | Rear Axle to Inside Box at Rear | 1017.5 mm | 40.1 in | 1017.5 mm | 40.1 in |
| H5 | SgRP-Front to Ground | 900.0 mm | 35.4 in | 908.7 mm | 35.8 in |
| H10 | SgRP-Second to Ground | 928.2 mm | 36.5 in | 936.8 mm | 36.9 in |
| H101 | Vehicle Height(curbLoad) | 1892.2 mm | 74.5 in | 1900.9 mm | 74.8 in |
| H103 | Front Bumper to Ground(curbwt.) | 256.2 mm | 10.1 in | 264.8 mm | 10.4 in |
| H105 | Rear Bumper to Ground(curbwt.) | 509.1 mm | 20.0 in | 517.7 mm | 20.4 in |
| H106 | Angle of Approach | 16.4 deg | 16.4 deg | 17.0 deg | 17.0 deg |
| H107 | Angle of Departure | 24.4 deg | 24.4 deg | 24.8 deg | 24.8 deg |
| H108 | Static Load-Tire Radius-Front* | 363.5 mm | 14.3 in | 372.1 mm | 14.6 in |
| H109 | StaticLoad-Tire Radius-Rear* | 363.5 mm | 14.3 in | 372.1 mm | 14.6 in |
| H130 | Step Height - Front(curbweight) | 529.3 mm | 20.8 in | 538.0 mm | 21.2 in |
| H131 | Step Height - Second(curbweight) | 551.0 mm | 21.7 in | 559.6 mm | 22.0 in |
| H147 | Ramp Breakover Angle | 16.2 deg | 16.2 deg | 16.9 deg | 16.9 deg |
| H148 | Suspension or Axel to Ground-Front | 190.2 mm | 7.5 in | 188.9 mm | 7.4 in |
| H153 | Suspension or Axel to Ground-Rear | 180.3 mm | 7.1 in | 224.9 mm | 8.9 in |
| H195 | Liftover Height | 1343.7 mm | 52.9 in | 1352.3 mm | 53.2 in |
| H250 | Open Tailgate to Ground | 838.0 mm | 33.0 in | 846.6 mm | 33.3 in |
| L101 | Wheelbase | 3567.8 mm | 140.5 in | 3567.8 mm | 140.5 in |
| L104 | Overhang-Front | 999.0 mm | 39.3 in | 998.9 mm | 39.3 in |
| L105 | Overhang-Rear | 1216.7 mm | 47.9 in | 1216.7 mm | 47.9 in |
| L114 | Front Wheel to Front SgRP c/l | 1474.6 mm | 58.1 in | 1474.6 mm | 58.1 in |
| L404 | Cab to Rear Axle | 936.5 mm | 36.9 in | 936.5 mm | 36.9 in |
| TRL3 | Rear Wheel Center line to Fuel Tank | 171.6 mm | 6.8 in | 171.6 mm | 6.8 in |
| W101 | Tire Track-front | 1742.4 mm | 68.6 in | 1742.4 mm | 68.6 in |
| W102 | Tire Track-rear | 1731.5 mm | 68.2 in | 1731.5 mm | 68.2 in |



[Site Map](#)

[Main Menu](#)

[Ram Home](#)

[PRINT](#)

[ALL](#)

[IN](#)

[OUT](#)