## 2013 TRUCK WHEELS, LUG NUTS & WHEEL VALVES

## 2013 Truck Wheels

WHEELS						
	COLOR					WEIGHT
P/N	CODES	SALES CODE	SIZE	DESCRIPTION	USAGE	(LB)
5GY15TRMAB	S4A	WD2	17 X 7.5 X 44.45MM	Steel Wheel	DJ 2,7/DD 3,8	37.45
52110366AD	SZ0	WGS	17 X 8.0 X 43.18MM	Chrome Clad Steel	DJ 2,7/DD 3,8 (AC NIK LVL TILL 10-31-12)	40.02
52122367AB	AAA	WFF	17 X 8.0 X 45.72MM	Forged Aluminum	DJ 2,7	23.8
1QR35TRMAA	AAA	WBG	17 X 8.0 X 43.18MM	Forged Aluminum	DJ 2,7	23.2
1HL36TRMAA	AAA	WFK	17 X 8.0 X 43.18MM	Forged Aluminum	DJ 2,7/DD 3,8	23.5
52121325AB	S4A	WF1	17 X 7.5 X 44.45MM	Spare	DJ 2,7/DD 3,8	37.45
1VU98TRMAA	S4A	WBN	18 X 8 X 57.15MM	Steel Wheel	D2 3,8	43.7
1UD26TRMAA	SZ0	WBH	18 X 8 X 57.15MM	Chrome Clad Steel	D2 3,8	45.2
1UD27TRMAA	AAA	WBJ	18 X 8 X 57.15MM	Forged Aluminum	D2 3,8	30.01
1UD29TRMAA	AAA	WBL	18 X 8 X 57.15MM	Cast Aluminum	D2 3,8	32.15
1VQ87TRMAA	AAA/GSA	WBA	18 X 8 X 57.15MM	Forged Aluminum	D2 3,8	31.41
1VQ87TRMAA	AAA/HWL	WBM	18 X 8 X 57.15MM	Forged Aluminum	D2 3,8	31.41
1VQ85TRMAA	DD5/CHROME INSERT	WRJ	20 X 8 X 54.65MM	Cast Aluminum	D2 3,8	39.16
1VQ86TRMAA	AAA/GSA	WRA	20 X 8 X 54.65MM	Forged Aluminum	D2 3,8	36.69
1VQ86TRMAA	AAA/HWL	WRK	20 X 8 X 54.65MM	Forged Aluminum	D2 3,8	36.69
68090830AA	E-COAT	WKN	18 X 8 X 57.15MM	Spare	D2 3,8	43.7
0ZZ23TRMAB	S4A	WFU	17X6.0X5.35	Dual Steel	D2 3,8 / DD 3,8 DRW	42.11
52121267AB	E-COAT	WD4	17X6.0X5.35	Dual Steel	D2 3,8 / DD 3,8 DRW	42.11
52121267AB	E-COAT	WD1	17X6.0X5.35	Dual Steel	D2 3,8 / DD 3,8 DRW	42.11
68079555AB/68081777AB	AAA	WF7	17X6.0X5.39	Forged Aluminum	D2 3,8 / DD 3,8 DRW	22.7
68079555AB/68081777AB	AAA	WF9	17X6.0X5.39	Forged Aluminum	D2 3,8 / DD 3,8 DRW	22.7
1CM11TRMAA	S4A	WP3	19.5X6.0X5.35	Dual Steel	DP 4,5,9,0	54
68053036AB/37AB	AAA	WP4	19.5X6.0X5.35	Dual Forged Aluminum	DP 4.5.9.0	27.49

19.5X6.0X5.36

4A, S4A = Argent

SZO Bright Chrome Plate PAK = Liquid Sparkle Silver

DX8 = High Glass Black

NA = Information not available at time of printing.

YFD = sparkle pewter

ALC = Alcoa REY = Reynolds

SUP = Superior

ARE = American Racing

HLA = Hayes Lemmerz aluminum

HLF = Hayes Lemmerz fabricated

MER = Meritor

Dual Spare

DP 4,5,9,0

2013 HF	MVV DII	TVILLO	MILITO
2013 HE	AVIDU	I Y I UKS	NULS

ZUIDILAVI DOTI EGGINGTO							
P/N	USED ON	DESCRIPTION	USAGE	TORQUE RANGE (NEWTON METERS)	RECOMMENDED TORQUE (NEWTON METERS)	WEIGHT PER NUT (LB)	
06509421AA SRW	VD2,VGS,VFF,VBG,VFK, VBN,VBH	M14x1.5, 60 DEGREES Uncapped	DJ2,77D23,87DD3,8 SRV	182-202	192	0.135	
06509422AA SRW	VBJ,VBL,VBM,VRJ, VRK,VBA,VRA	M14x1.5, 60 DEGREES Capped	D2 3,8	182-202	192	0.166	
06509424AA DRW	WFU , WD4 ,WF7 , WF9 , WP3 ,WP4 ,WKG	M14x1.5, w/ washer	D2 3,8/DD 3,8/DP 0,4,5,9 DRW	180-200 DP 182-202 D2,DD	190 DP-192 DD,D2	0.263	

C/O DRW

2013 HEAVY DUTY VALVES						
P/N	USED ON	DESCRIPTION	USAGE	WEIGHT PER VALVE (LB)		
52057949AC RUBBER	WD2,WGS,WFF,WBG, WFK,WF1,WFU,WD4, WBN,WBH,WBJ,WBL, WBM,WBA,WRJ,WRK, WRA,WKN	VALVE-600 HP	DJ 2,7 / D2 3,8 / DD 3,8	0.003		
02530152 1" EXT FOR RUBBER VALVE	WD4,WF7		D2 3,8 / DD 3,8			
02530153 1.5"EXT FOR RUBBER VALVE	WD4,WF7		D2 3,8 / DD 3,8			
52013869AA BRASS DP ONLY	WP3,WKG	VALVE TR416S	DP 4,5,9,0	0.055		
52013910AA BRASS EXTENSION DP ONLY	ALL	EXT - VALVE	DP 4,5,9,0	0.010		
68053042AA NICKEL ALUMINUM DRW ONLY	WP4,WF7,WF9	VALVE TR545C	D2 3,8 / DD 3,8 / DP 4,5,9,0	0.001		









## 2013 TRUCK WHEELS, LUG NUTS & WHEEL VALVES

## 2013 DS Truck Wheels, Lug Nuts and Wheel Valves

	COLOR					WEIGHT
P/N	CODES	SALES CODE	SIZE	DESCRIPTION	USAGE	(LB)
1UC54TRMAA	S4A	WFP	17 X 7.0 X 25.4	Steel Painted	DS 1, 6	27.0
1UB12TRMAA	GSA	WFE	17 X 7.0 X 25.4	Cast Aluminum Painted	DS 1, 6	24.8
1UB16TRMAA	SZ0	WFJ	17 X 7.0 X 25.4	Cast Alum. Chrome Clad	DS 1, 6	27.1
1UB17TRMAA	GSA	WRE	20 X 8.0 X 19.05	Cast Aluminum Painted	DS 1, 6	33.0
1UC56TRMAA	SZ0	WRK	20 X 8.0 X 19.05	Cast Alum. Chrome Clad	DS 1, 6	35.1
1DY13TRMAC	SZ0	WP2	20 X 9.0 X 19.05	Cast Alum. Chrome Clad	DS 1, 6	34.2
1UB18TRMAA	GSA	WRF	20 X 9.0 X 19.05	Cast Al. Polished/Painted	DS 1, 6	33.2
1UB19TRMAA	SZ0	WRG	20 X 9.0 X 19.05	Cast Alum. Chrome Clad	DS 1, 6	32.2
1UB20TRMAA	HWL	WRH	20 X 9.0 X 19.05	Cast Al. Polished w/ Inserts	DS 1, 6	34.5
1UB20TRMAA	GSA	WRJ	20 X 9.0 X 19.05	Cast Al. Polished w/ Inserts	DS 1, 6	34.5
52014257AA	AAA	WPZ	22 X 9.0 X 19.05	Forged Aluminum Polished	DS 1, 6	34.9
68089775AA	E-Coat	WF1	17 X 7.0 X 25.4	Steel Spare	DS 1, 6 (spare only)	27.0
05290568AA	E-Coat	WGA	20 X 8.0 X 19.05	Steel Spare	DS 1, 6 (spare only)	40.0

S4A = Argent

SZ0 = Bright Chrome Plate

GSA = Tech Silver

HWL = White Gold

AAA = Polish

				TORQUE RANGE	RECOMMENDED	WEIGHT PER
P/N	USED ON	DESCRIPTION	USAGE	(LB-FT)	TORQUE (LB-FT)	NUT (LB)
		M14x1.5, 60				
06509422AA	ALL	DEGREES Capped	DS 1,6	125 - 145	135	0.135

				WEIGHT PER
P/N	USED ON	DESCRIPTION	USAGE	VALVE (LB)
56029398AB	ALL	TPM Sensor	DS 1,6	0.073
		433.92 MHz Snap-in		
02073355	ALL	VALVE TR413	DS 1,6 (spare only)	0.024





