

“Rear View Camera Installation”

The RAM Chassis Cab is offered with a rear camera option package sales code XAC. Included in this option package are a 10ft video cable (part number 68200274AA) and a user mountable camera (part number 56038978AF). Also, a 30ft. cable is available for purchase from Mopar, part number 68239372AA. The camera output will be viewable either via video pane in the rear view mirror, or a video screen in the radio, depending on the vehicle options.

This Jumper-Camera kit is packaged within the upfitter bag located behind the driver's seat (items in bag are separate).



To install, first remove the video cable and the camera from the upfitter bag, extend the cable to locate both end-connectors. Install the *white* connector from jumper onto the camera connector mate as shown in the pictures. A 'click' will be heard when a secure connection has been achieved.



2014 REAR VIEW CAMERA INSTALLATION

11/26/2013

Route the video cable as desired, taking care to prevent in-use impact/abrasion damage. Add a protective covering (such as convolute) if prudent. Secure the cable (using clips/straps) often in its routing path. Install the *black* connector onto its chassis harness mate, located at the rear of the vehicle. A 'click' will be heard when a secure connection is achieved.

Chassis harness camera connector located on rear face of rear-most chassis cross-member.



Chassis harness connector with protective cap removed. NOTE: This connector may be routed behind other harness wiring at this location and therefore somewhat difficult to see.



“Rear View Camera Installation”